



**EPILAY™ EPISTIK™ ICE & WATER
SELF ADHERED ROOFING UNDERLAYMENT**

**TOP OF THE LINE PREMIUM HEAVY DUTY
REPLACEMENT FOR TRADITIONAL PEEL
AND STICK ROOFING UNDERLAYMENT**



Epilay™ EpiStik™ Ice & Water Roofing underlayment with its advanced engineering is highly recommended for Self Adhered Peel & Stick applications for sloped roofs. It is a granulated fiberglass reinforced SBS modified bitumen membrane, it is ideal for use under Asphalt Shingles, Tiles, Shakes & Metal Roofing. Epilay™ EpiStik Ice & Water is a Top of the line Premium Heavy Duty underlayment.

Epilay™ EpiStik™ Ice & Water Hi Temp Underlayment can be used under primary roofing materials.

**CONTACT US
FOR MORE INFORMATION**

EMAIL sales@epilay.com
WEB www.epilay.com



CCRS - #1083



No.: FL22316



Top of the Line Premium Heavy Duty Replacement for Traditional Peel & Stick Roofing Underlayment

Epilay™ Epistik™ Ice & Water Roofing underlayment with its advanced engineering is highly recommended for Self Adhered Peel & Stick applications for sloped roofs. It is a granulated fiberglass reinforced SBS modified bitumen membrane, it is ideal for use under Asphalt Shingles, Tiles, Shakes & Metal Roofing. Epilay™ EpiStik Ice & Water is a Top of the line Premium Heavy Duty underlayment.

Epilay™ EpiStik™ Ice & Water HI TEMP Underlayment can be used under primary roofing materials.



Epilay™ EpiStik™ Ice & Water adhesive layer is made from the advanced SBS Modified Bitumen based adhesive which performs extremely well in high as well as low temperatures and gives excellent adhesion to the primary roofing surface. The temperature performance range for Epilay EpiStik™ Ice & Water is -40° F to 250° F. (-40°C to 121° C)

EPILAY™ EPISTIK™ ICE & WATER IS A GRANULATED FIBERGLASS RE-INFORCED SBS MODIFIED BITUMEN UNDERLAYMENT:

- Water repellant, non- absorbent and UV resistant for up to 90 days.
- **Unique 3" Overlap Edge for excellent adhesion in overlaps**
- 55 mil thickness.
- Ice Dam Protection
- Florida Building Code Approved
- HIGH-TEMP
- Class A Fire Rating as per ASTM E 108
- Excellent rollability
- Works best for use under Metal, Shake, concrete tiles, slates & asphalt shingles.
- Does not wrinkle , crack or become stiff in colder temperatures for smooth and easy installation
- Epilay™ EpiStik Ice & Water will not dry out or leach oil in high heat environment.
- Limited Life time limited warranty
- Temperature performance range -40°F to 250°F (-40°C to 121°C)

EPILAY™ EPISTIK™ ICE & WATER SPECIFICATIONS

Length Per Roll	65'	Squares Per Roll	2
Width Per Roll	36"	Rolls Per Pallet	25
Weight Per Roll	55 lbs	Gr. Weight Per Pallet	1425 lbs

EPILAY™ EPISTIK™ ICE & WATER TECHNICAL DATA

TEST PROPERTIES	TEST STANDARD	EPISTIK PLUSTYPICAL VALUES
Unrollability	ASTM D 1970	No cracking, tearing, or damage
Thickness Mils	ASTM D 5147	55 mils
Tensile Strength	ASTM D 1970	MD32/CD27
Adhesion to Plywood lb/ft	ASTM D 1970	
40° F		6.1
75° F		27.8
Thermal Stability	ASTM D 1970	250° F/Pass
Low Temperature Flexibility	ICC AC 48	Pass
Tear Resistance lb/ft	ASTM D 1970	MD153/CD137
Permeability	ASTM E 96	0.03
Nail Sealability	ASTM D 1970	Pass