



SELF ADHERED ROOFING UNDERLAYMENT



Technical Data Sheet

TEST PROPERTIES	TEST STANDARD	TYPICAL VALUES
UNROLLABILITY	ASTM D1970	NO CRACKING, TEARING OR DAMAGE
THICKNESS MILS	ASTM D 5147	(Nominal) 55 mils
TENSILE STRENGTH	ASTM D 1970	MD32/CD27
ADHESION TO PLYWOOD LB/FT	ASTM D 1970	-
40° F	-	6.1
75° F	-	27.8
THERMAL STABILITY	ASTM D 1970	250F /Pass
LOW TEMPERATURE FLEXIBILITY	ICC AC 48	PASS
TEAR RESISTANCE LB/F	ASTM D 1970	MD153/CD137
PERMEABILITY	ASTM E96	0.03
NAIL SEALABILITY	ASTM D 1970	PASS

SPECIFICATIONS :	DATA
LENGTH PER ROLL	65'
WIDTH PER ROLL	36"
WEIGHT PER ROLL	55 LBS
SQUARES PER ROLL	2
ROLLS PER PALLET	25
GR. WEIGHT PER PALLET	1425 lbs



For more information visit our website at www.epilay.com or
 Contact our Marketing Dept. at sales@epilay.com