



ProtectTite™ SUPERIOR



ROOFING UNDERLAYMENT

Epilay™ ProtecTite™ Superior Roofing Underlayment with its advanced engineering is highly recommended for mechanically attached, coated woven synthetic roofing underlayment for sloped roofs. Epilay™ Superior is specifically manufactured to replace the #15 felt and #30 felt.

Epilay™ Superior is 25 times stronger than #15 felt and #30 felt and 4x lighter than #15 felt and #30 felt. With a 7mil thickness, a 10 square roll weighs only 23 lbs! This super low weight combined with 48" width and 250 ft. run length means big savings in time and labor - over 30% faster to install than felt!

These unique design features, when coupled with Epilay™ Superior's exceptional light weight and exceptional tear strength, allows the contractor to easily carry the roll up and down the ladder. Fewer laps, cuts, and roll handling means you can do more jobs in less time resulting in huge savings for you, the roofing contractor.

EPILAY™ PROTECTITE™ SUPERIOR 4-LAYER CONSTRUCTION

PP NON-WOVEN GRAY
COOL SURFACE GRIPWALK™

BONDING PP LAYER

PP CROSS WOVEN SCRIM

SKID-RESIST™
HIGH ANTI-SKID LAYER



Epilay's™ GripWalk™ high-traction unique gray top layer provides for a cooler working surface and can be used under primary roofing materials to replace 30# felt. GripWalk™ high traction walking surface permits easier steep slope walkability, even during high condensation or moisture on the surface.



Epilay's™ Skid-Resist™ is a very high anti-skid bottom surface made using superior technology and advanced polymers to help keep the underlayment intact and prevent the fabric from tearing while it is being fastened, avoiding any leakages through the underlayment layer.

Epilay™ Superior is a 100% synthetic composition providing the following benefits to the roofing contractor:

- 1 year UV protection
- Water repellant, non-absorbent
- 7 mil thickness
- Works best for use under Asphalt Shingles & Residential Metal
- Does not wrinkle, crack or become stiff in colder temperatures for smooth and easy installation
- Epilay™ Superior will not dry out or leach oil in high heat environments as organically saturated felts do
- 4 times lighter and 25 times stronger than #15 felt and #30 felt
- 20 year limited warranty
- Class A Fire ASTM EI 08 - Meets & exceeds ASTM D4869 and D226
- Synthetic construction impervious to mold growth
- Superior 4 ply underlayment (3 ply cross-woven coated polypropylene with a layer of non-woven polypropylene)
- Strong and durable polymer construction
- 100% recyclable
- Temperature performance range -40°F to 260°F (-40°C to 126°C)



Intertek

AC-188 CRR# 1004



NOA No. 18-1126.09



No.: FL16850



CAN-CSA Approved

For more information visit our website at www.epilay.com or
Contact our Marketing Dept. at (800) 292-6728 or sales@epilay.com.

Member of: **SRUI**
SYNTHETIC
ROOF
UNDERLAYMENT
INSTITUTE